

**SPECIFICATIONS**

Capacity: 12,000 lbs. **Trailer Weight:** 4,200 lbs.

Deck Width	8 ft. Length: 16 ft. 6 in. Height: 34 in.
Frame	Mainrails: W12" x 16 lbs. wide flange I-Beam, one piece cold formed Hi-tensile 50,000 P.S.I. steel mainrails from front to drawbar to rear of trailer
Crossmembers	6" x 3.7 lbs. per ft. I-Beam
Decking	Nominal 2" Hardwood
Headboard	8" high, full width of trailer Drawbar Storage Area
Lights	12 volt, DOT approved
Wiring Harness	USA Star PLUS Sealed Modular Wiring Harness w/ 7-Way ATA Plug
Hitch	One piece solid cast steel (adjustable) lunette eye & flange mount
Safety Chains	Two 3/8" Blue-Krome plated high test, Safety Hook w/ Latch
Parking Jack	12,000 lbs. static / 10,000 lbs. lift (Heavy Duty drop leg screw type)
Tie Down	Four per side - Patented "ROTO RINGS"® Swivel 360°
Colors	Yellow (Standard), Red, Black

RUNNING GEAR

Tires	Four 235/80R16 (E)
Hubs/Wheels	Four 8 Stud on 6 1/2 BC Hubs, Four Disc Type Wheels 6.00 x 16
Suspension	Nylon bushed slipper spring w/ equalizer, capacity 12,000 lbs. tandem
Axles	Two Dexter 6,000 lbs. each
Brakes	Dexter 12' x 2' electric each wheel
Break-away	12 Volt, wet cell battery with integrated battery charging system

OPTIONS

- Spare Tire & Disc Wheel 235/80R16 (E) Optional: Spare Tire Carrier
- Tool Box Lid (Lockable) Optional: Expanded Metal Tray Plate
- Traction 2" x 2" Angle 6" C/C Wheel Paths Optional: Traction Center Section, Bucket Pocket or Plate
- Ramps Ladder (standard) Wood (Optional N/C)
- Brake Controller: Cab mounted w/ complete truck wiring harness and receptacle
- Paint (other than standard Black, Yellow, Blue) Price on Request

